

UNI EN ISO 6931-1:2020

Diametro mm	RESISTENZA N/mm ²			
	1.4310 NS	1.4310 HS	1.4401	1.4568
	Min / Max	Min / Max	Min / Max	Min / Max
$d \leq 0,20$	2200 / 2530	2350 / 2710	1725 / 1990	1975 / 2280
$0,20 < d \leq 0,30$	2150 / 2480	2300 / 2650	1700 / 1960	1950 / 2250
$0,30 < d \leq 0,40$	2100 / 2420	2250 / 2590	1675 / 1930	1925 / 2220
$0,40 < d \leq 0,50$	2050 / 2360	2200 / 2530	1650 / 1900	1900 / 2190
$0,50 < d \leq 0,65$	2000 / 2300	2150 / 2480	1625 / 1870	1850 / 2130
$0,65 < d \leq 0,80$	1950 / 2250	2100 / 2420	1600 / 1940	1825 / 2100
$0,80 < d \leq 1,00$	1900 / 2190	2050 / 2360	1575 / 1920	1800 / 2070
$1,00 < d \leq 1,25$	1850 / 2130	2000 / 2300	1550 / 1790	1750 / 2020
$1,25 < d \leq 1,50$	1800 / 2070	1950 / 2250	1500 / 1730	1700 / 1960
$1,50 < d \leq 1,75$	1750 / 2020	1900 / 2190	1450 / 1670	1650 / 1900
$1,75 < d \leq 2,00$	1700 / 1960	1850 / 2130	1400 / 1610	1600 / 1840
$2,00 < d \leq 2,50$	1650 / 1900	1750 / 2020	1350 / 1560	1550 / 1790
$2,50 < d \leq 3,00$	1600 / 1840	1700 / 1960	1300 / 1500	1500 / 1730
$3,00 < d \leq 3,50$	1550 / 1790	1650 / 1900	1250 / 1440	1450 / 1670
$3,50 < d \leq 4,25$	1500 / 1730	1600 / 1840	1225 / 1410	1400 / 1610
$4,25 < d \leq 5,00$	1450 / 1670	1550 / 1790	1200 / 1380	1350 / 1560